ARMORED MERCEDES-BENZ S 580

NEW GENERATION BODY STYLE



LEVEL A9/B6+

AGAINST 7.62 x 39mm, 5.56 x 45mm, 7.62 x 51mm





BASE CHASSIS SPECIFICATIONS

MAKE: Mercedes-Benz

MODEL: S 580 4MATIC

ENGINE: 4.0L V8 Biturbo Petrol

POWER: 496 hp & 516 Torque LB-FT

TRANSMISSION: 9G-Tronic 9-Speed Automatic

TIRES: 19 in (W/Run-Flat System)

COLOR: Black

INTERIOR: Black Nappa Leather

SEATING: 2 + 3

APPROX. WEIGHT: 6,400 lbs. (2,902 kg)

HEIGHT:

59 in.

(149 cm)

WIDTH:

83 in.

(210 cm)

LENGTH:

204 in.

(518 cm)

WHEELBASE:

122 in.

(309 cm)









Firewall

Ballistic steel or composite material firewall provides protection from explosion and different angle of attacks.

3-1

Roof

Roof is lined with ballistic steel or composite to protect against penetration at an angle and vehicle stability.





Floor

Floor is lined with ballistic steel or composite to protect against mines and grenade blasts.

3-3

Doors

All doors are made from ballistic steel or composite material.






Battery Protection

Fully enclosed in serviceable ballistic steel casings.

3-5

Rear VIP Protection

Customized ballistic rear section completely made out of certified ballistic steel.





Overlaps

All doors and windows feature ballistic steel overlaps to keep shrapnel from angle shots from entering the cabin.

3-7

Wheel Wells

Front and rear wheel wells are lined with ballistic steel.






* Tel: +1.703.471.0002 * Fax: +1.703.471.0202 * www.alpineco.com * sales@alpineco.com *



Glass Armor

Minimum 40 mm thick glass/polycarbonate composite A9/NIJ III transparent armor installed on the vehicle.

4-1



Anti-Spall Layer

Inner-most anti-spall layer prevents glass and bullet fragments from penetrating into passenger cabin area and is free of any optical distortion and discoloration.



Multi-Hit Protection


All windows are capable of sustaining multiple hits while providing protection to passengers.

4-3



Customized Actuators

The front 2 windows are equipped with special customdesigned heavy duty actuator mechanism to allow for faster and quitter operation with maximum traveling distance.





P.A./Multi-Siren System

Located on the center console. The multi-siren features standard siren tones, volume adjustment, and a public address system.

5-1

Battery Protection

The battery is encased in a ballistic steel box to protect it.





Power Windows

The front driver and passenger window are powered and lower approximately 4 - 6 inches.

5-2

Fuse Box Protection

The fuse box is protected by a ballistic steel box.





Rear VIP Protection

Ballistic Steel Bulkhead behind rear seats protecting incoming rounds

5-3

Fuel Tank Protection

Fuel tank is protected by a ballistic steel box. Protects from two simultaneous grenades.





Run-Flat Inserts

Vehicle will be equipped with full-size run-flat inserts in each tire.

5-4

Tailpipe Protection

The tailpipe features a special mesh that prevents the tailpipe from being sabotaged.





* Tel:+1.703.471.0002 * Fax:+1.703.471.0202 * www.alpineco.com * sales@alpineco.com *



Upgraded Braking

The vehicle's braking system (rotors & pads) will be upgraded to accommodate the added armor weight.

6-1

WiFi/HotSpot/Sunroof Delete

Following Items will be deleted upon completion:

Sunroof/Moonroof





Ballistic Door Overlap

Each door is equipped with ballistic steel overlap with added custom bullet-catchers wrapped in high quality leather or vinyl.

6-2

OEM Air Ride Suspension

Auto 4-wheel level control helps compensate for additional cargo or passengers. It also lowers the ride height at higher speeds for improved aerodynamics, stability and efficiency.





OEM Appearance

The exterior of the vehicle with the VIP Armoring conversion will maintain the OEM appearance of the factory vehicle.

6-3

External Car Microphone

Sleek, low profile microphone installed in the exterior of the vehicle (so you don't open your windows to speak).

6-7





P.A./Multi-Siren System

Located on the center console. The multi-siren features standard siren tones, volume adjustment, and a public address system.

6-4

Emergency Lights Package

Alpine will install flashing Red/Blue LED lights hidden in the front grille and wired to the PA controller.

















"no one protects you **better.**"

























"no one protects you **better.**"

ALPINE ARMORING INC.

ALPINE ARMORING'S BALLISTIC CHART

A											"no one protects you better"	
WEAPONS	SPECS			LEVELS				BULLETS			NUMBER OF SHOTS	
WEATONS	ТҮРЕ	CALIBER (mm)	CLASS	STANAG	UL	ALPINE	NIJ	CEN	MASS (g)	MATERIAL	VELOCITY	HOMBER OF SHOTS
	.38 Special	9 x 19	Handgun	-	1	A1	I.II.IIA	-	8.00	FCC1	358 M/S	-
	.357 Magnum	9 x 33	Handgun	-	2	A2	I.IIA	B1 & B3	10.20	JSP	430 M/S	5
	.44 Magnum	11 x 33	Handgun	-	3	A3	IIIA	B4	15.60	LWC	440 M/S	
177	MP5	9 x 19	SMG	-	6	A4	IIIA	B2	8.00	LCO	427 M/S	, —
	Shotgun	12 Gauge	Shotgun	-	3 & 4	Aa	IIIA	SG2	28.30	SLUG	503 M/S	3
	Tokarev	7.62 x 25	Handgun	-	-	A5	IIIA	-	5.50	rcs i	488 M/S	
-	Kalashnikov (AK-47)	7.62 x 39	Assault Rifle		-	A6	III	B5	9.70	2CC1	732 M/s	
-	Kalashnikov (AK -47 Military)	7.62 x 39 API BZ	Assault Rifle	11	-	A7	_	B5+	11.70	2001	774 M/s	
Part !	M16/AR-15	5.56 x 45 NATO SS109 5.56 x 45 NATO Ball	Assault Rifle	1	7	A8	IV	B5	4.00	rcci 2cci	900 M/S 833 M/S	3
	Winchester .308	7.62 x 51	Rifle	1	7	A9	III	B6	10.90	rcci	810 M/S	-
	Remington 700 SPS	742 × 63 AP (.30-06)	High-Power Rifle	III	5 & 8	A10	IV	B7-	10.80 8.40	AP	869 M/s 930 M/s	5
	Dragunov	7.62 x 54R B32 API	Sniper Rifle	111	-	A11	IV+	B7+	10.04	2001	854 M/s	
	,50 Cal	12.7 x 99	High-Power Rifle	IV	10	A12	_	-	45.00	CI	908 M/S	
	- 30											



UL Underwriters Laboratory, 752

NIJ National Institute of Justice, 0108.01

CEN European Standard

STANAG ... NATO's Standard (STANAG 4569)

ALPINE Alpine Armoring's Certified Standard

LCCJ Lead Core Copper Jacket

JSP Jacketed Soft Point LWC Lead Wad Cutter

LCSJ Lead Core Steel Jacket

SCCJ Steel Core Copper Jacket

AP Armor Piercing

SG Shotgun

Shots (5) 11.4 cm Square Pattern (Corners & Center)

Shots (3) 11.4 cm Triangular Pattern

Velocity Minimum Measured Velocity

NIJ Rating .. Levels I, II, IIA, & IIIA (based on 1 of 2 required calibers of ballistic threat)









* Tel: +1.703.471.0002 * Fax: +1.703.471.0202 * www.alpineco.com * sales@alpineco.com *